

# Suppression Settings

In this section:

- [suppression{n}.file.ext](#)
- [suppression{n}.comment](#)
- [suppression{n}.comment.suffix](#)
- [suppression{n}.block.only](#)
- [suppression.local.dir](#)

## suppression{n}.file.ext

This setting specifies the extension file types that should be scanned for suppression comments.

### Acceptable Values

<code>[file extension]</code>	The extension of files that will be searched for suppressions.
-------------------------------	--

### Example Usage

The following configuration searches `.xml` and `.java` files for suppression comments:

```
suppression1.file.ext=xml
suppression2.file.ext=java
```

### Related

- [Suppressing the Reporting of Findings](#)
- 

## suppression{n}.comment

This setting specifies the prefix for suppression comments for files specified with the [suppression{n}.file.ext](#) property.

### Acceptable Values

<code>[comment marker]</code>	The prefix marker for suppression comments.
-------------------------------	---

### Example Usage

The following configuration specifies the `//` and `<!--` prefixes of suppression comments:

```
suppression1.comment=//
suppression2.comment=<!--
```

### Related

- [Suppressing the Reporting of Findings](#)
- 

## suppression{n}.comment.suffix

This setting specifies the suffix for suppression comments for files specified with the [suppression{n}.file.ext](#) property. If this setting is not configured, suppression comments will not be suffixed.

### Acceptable Values

<code>[comment marker]</code>	The suffix marker for suppression comments.
-------------------------------	---

### Example Usage

The following configuration specifies the --> suffix of suppression comments:

```
suppression1.comment.suffix-->
```

## Related

- [Suppressing the Reporting of Findings](#)
- 

## suppression{n}.block.only

This setting enables or disables block-only comment suppressions support for files specified with the [suppression.file.ext](#) property.

### Acceptable Values

<b>true</b>	The block-only comment support for suppressions is enabled.
<b>false</b>	Default. The block-only comment support for suppressions is disabled.

The following configuration enables the block-only comment support for suppressions.

```
suppression1.block.only=true
```

## Related

- [Suppressing the Reporting of Findings](#)
- 

## suppression.local.dir

This setting specifies the custom directory for storing local suppressions. An absolute path should be provided.

### Acceptable Values

<b>[path]</b>	The path to the folder where local suppressions will be saved.
---------------	--

### Example Usage

The following configuration stores local suppressions in the 'suppressions' folder:

```
suppression.local.dir=C:\parasoft\suppressions
```

## Related

- [Suppressing the Reporting of Findings](#)