

Installing the Server

The installation procedure depends on which servlet container you're deploying it to. There are also multiple ways to install servers on any given servlet container. In all instances:

1. Install the server into its own dedicated container (e.g., not shared with another web application)
2. Deploy the WAR file at the root context of the servlet container.
3. The server should run as a different user than the system user.

Installing Parasoft Virtualize Server on the Same System as Parasoft CTP

If you are installing the SOAtest and Virtualize Server on the same system as Parasoft CTP, be sure to install the server into its own dedicated servlet container.

Prerequisites

OS	Windows, MacOS, and Linux are supported. For specific OS versions, refer to the system requirements sections in the SOAtest Desktop Installation and Virtualize Desktop Installation chapters.
Software	Java 8
Servlet containers	<p>The following servlet containers have been tested and are supported for SOAtest and Virtualize Server WAR file deployments:</p> <ul style="list-style-type: none">• Apache Tomcat 7• Apache Tomcat 8• Jetty 9.3.14 and sub minor versions later than 9.3.14 (9.4.x and versions prior to 9.3.14 are not currently supported)• WildFly 10.1 or higher• WebSphere 8.5.5 <p>Although the WAR file may be deployed to other servlet containers, Parasoft only supports the containers specified in this documentation and cannot guaranty that the server will start or function as expected when deployed to other containers.</p>

Clustering is not supported.

Deployment Examples

- [Apache Tomcat Example Deployment](#)
- [Jetty Example Deployment](#)
- [WebSphere Example Deployment](#)
- [WildFly Example Deployment](#)