

# Installation 1

Jtest DTP Engine is distributed as a ZIP installation package.

1. Extract the package to the desired location. The `jtest` directory (`[INSTALL_DIR]`) that contains all Jtest files will be created.
2. Ensure that the `JAVA_HOME` variable is set in your environment.

No additional steps are required, but for your convenience, we recommend that you:

- Add the `[INSTALL_DIR]` path to `$PATH` or symlink `jtestcli.exe` (`jtestcli` in Linux) into the directory in `$PATH`.
- Set the `$JTEST_HOME` environment variable that points to the `[INSTALL_DIR]` path.

## If you use Maven

Set the following properties in your Maven `settings.xml` file:

- `pluginRepository`
- `groupId,`
- `jtest.home`

For details, see the Parasoft Jtest Plugins manual located in `[INSTALL_DIR]/manuals`. Open the `plugins-manual.html` file and select **JTEST MAVEN PLUGIN> Usage> Initial Setup**.

## If you use Ant

Deploy `[INSTALL_DIR]/integration/ant/jtest-ant-plugin.jar` into the `$ANT_HOME/lib` directory.

For details, see the Parasoft Jtest Plugins manual located in `[INSTALL_DIR]/manuals`. Open the `plugins-manual.html` file and select **JTEST ANT PLUGIN> Usage> Initial Setup**.