

Eclipse p2 Update Site Installation

This topic explains how to install SOAtest from a Eclipse p2 update site.

Installation

When installing from the update site, you need to install the Eclipse Graphical Editing Framework (GEF). You can download and install Eclipse GEF from <http://www.eclipse.org/gef/>.

1. Launch Eclipse and choose **Help> Install New Software**.
2. Add the p2 update site zip file as follows:
 - a. Click the **Add** button. An Add Site dialog will open.
 - b. In the dialog's **Name** field, type `Parasoft`.
 - c. To the right of the **Location** field, click the **Archive** button, then browse to the appropriate zip file (obtained via your Parasoft representative).
 - d. Click **OK**. The Install panel will display the available features.
3. Select the features that you want to install, then click **Next** and follow the prompts to complete the installation process.
4. (Recommended) Restart the application.

When installing Parasoft SOAtest from the p2 update site on Windows, it is necessary to run the .bat script named `soatest_install.bat`. This script is installed into the `eclipse` directory of the Eclipse installation into which you installed the update site. It registers some DLLs that are needed for web functional testing using Internet Explorer. It executes tasks that are normally completed by the Parasoft installers, but are not supported by the p2 update site. This script must be run as administrator.

Mac OS Installation Using the Eclipse Installer

If you have installed Eclipse on Mac using the Eclipse installer, you will need to start Eclipse from the command line before using the update site.

A valid license is required. See [Licensing](#) for details on configuring your license.