

Customizing Import Options

You can set import parameters, such as priority level and severity level, that determine which findings are imported into the IDE.

1. Click **Parasoft** in the menu bar and choose **Options**.
2. Select **Import Findings and Coverage**.
3. Choose your import options. The available options are described below.
4. Click **Apply** to save your settings.

Available Options

The following options are available:

The screenshot shows the 'Import Findings and Coverage' options dialog. At the top, there is a checked checkbox for 'Automatically import findings at a specific time:' followed by two dropdown menus set to '09' and '00'. Below this is a section titled 'General options' containing: a checked 'Severity' checkbox with radio buttons for '1 - Highest', '2 - High', '3 - Medium', '4 - Low', and '5 - Lowest'; a checked 'Assigned to' checkbox with a text field containing 'annstu' and a checked 'Default' checkbox; and an unchecked 'Suppressed findings from local analysis or file' checkbox. The next section is 'DTP options', which includes: a 'Filter' dropdown menu set to 'Jtest'; a checked 'Priority' checkbox with radio buttons for 'Critical', 'High', 'Medium', and 'Low'; a 'Due by' section with three dropdown menus set to 'April', '18', and '2017'; and a checked 'Limit' checkbox with a text field set to '500'.

Automatic Import

- **Automatically import findings at a specific time:** If you want to automatically import findings from DTP once a day, enable this option, then specify the time when the automatic import should begin. If your IDE is closed at the time you specified, the automatic import will begin on startup. This option is disabled by default.

General Options

- **Severity:** By default, all finding severities are selected. To specify which findings to import according to severity level, enable the **Severity** option and select your options.
- **Assigned to:** Findings assigned to the local user are imported by default. To import findings assigned to a different user, enable the **Assigned to** option and specify the appropriate user name. See the [Configuring Authorship](#) in Automation User Guide for information on how to configure finding assignment.
- **Suppressed findings from local analysis or file:** When this option is enabled, findings that have been suppressed are loaded to the Findings view along with regular findings (see [Suppressing Findings](#)).

DTP Options

- **Filter:** To import only data associated with a specific DTP filter, choose a filter from the **Filter** drop-down menu. Filters are identifiers used in DTP for organizing data (see [Automation User Guide](#) for more information).
- **Priority:** By default, all priority levels are imported. To import findings according to a specific priority level, enable the **Priority** option and choose which findings to import.
- **Due by:** To import all violations that are due any time between the present date and the date specified--not just the violations due on that date, enable the **Due by** option. See [Finding Properties](#) for additional information about the Due Date category.
- **Limit:** To limit the number of findings imported, enable the **Limit** option and enter a value in the field.